



## Air Lucky (v13.2) #81218-1

Thank you for purchasing a Lucky Duck™ Premium Decoy. To view additional Lucky Duck™ products please visit your local Sporting Goods dealer or online at [www.luckyduck.com](http://www.luckyduck.com).

Unpack the contents of the carton your Air Lucky came in. You should have the following components.

- a. Right and Left Wing
  - b. Air Lucky body
  - c. Threaded wing shaft
  - d. 3-piece stake
  - e. Bag of feet and mounting hardware, plastic mounting bracket
- 2) Remove the feet and wing nuts from the poly bag and remove the rubber guards from the foot posts on the decoy body. You can discard the rubber shipping guards. Install the feet with the "thumbs" pointed inward over the posts and secure in place with the provided wing nuts.
  - 3) Locate the threaded shaft. On each end of the shaft, close to the threads, will be an L and an R printed. This indicates Right and Left. Right and left are determined as if you were the decoy or standing behind the decoy looking forward. Locate the Left wing. On each wing will be a small L or a R molded. You will find this on the white part of the wing close to the inside edge in the inward curve.
  - 4) Thread the Left wing onto the left end of the threaded shaft. When threading the wing onto the shaft, the wing should turn backward, the same way it would spin when functioning in the field.
  - 5) Insert the other end of the threaded shaft into the hole on the left side of the decoy and feed it out the right side hole.
  - 6) Install the remaining Right wing, also turning backward until tight...this will be opposite of a normal right-handed thread. You will need to grasp the shaft on the left side to perform this task.
  - 7) Best performance in low winds will be achieved by aligning the wings 90° to each other to the wing is always catching a wing blade. It will work if the wings are aligned as well, but perform better if they are 90° to each other.
  - 8) Assemble the 3 part stake by starting with the smallest diameter and depressing the spring button and sliding it inside the next largest diameter tubing. You will need to align the tubing so the holes line up with the spring buttons. Slide the sections together until the spring button snaps in place and then secure with the thumbscrew. Repeat this for the top section. The largest T-shaped section is the top section.
  - 9) Locate the plastic mounting bracket. It will have a round ball and a round end. Slide the base of the pivot bracket into the top of the 3 piece stake and secure with the provided thumbscrew.
  - 10) Insert the round end into the hole in the chest of the decoy.

### TIPS:

- 1) You may find better and quieter performance in low winds if you use a little Teflon lubrication or graphite powder in the wing bushings.

**Lucky Duck™ warrants this product against all manufacturing defects for a period of 1 year from date of purchase. Proof of purchase is required. Abuse of the product (submerged in water, dropped, mistreatment etc.) is not covered. Please return and exchange the defective unit to the store where you purchased the product. If the store will not accept the return, please call customer service at 715-338-3183.**



**Lucky Duck™**  
A Division of Expedite International Inc.  
1950 8<sup>th</sup> Ave  
Baldwin, WI 54002  
Customer Service 715-338-3183  
[www.luckyduck.com](http://www.luckyduck.com)